

KENWOOD

Listen to the Future



TK-7162E/8162E

VHF/UHF FM Mobile Radios

5-tone **FleetSync**
KENWOOD

Kenwood's TK-7162/8162 mobiles provide the performance, power and quality for reliable communications in a wide range of mobile applications and environments. User-friendly features include a 16-channel capacity, 5-Tone signalling, FleetSync® and easy-to-see backlit LCD.

NEW CONCEPT DESIGN

Kenwood employed premium industrial design concepts to make the TK-71 62/8162 functionally practical, rugged and an attractive piece of equipment to use.

MIL-STD 81 0C/D/E/F

The TK-71 62/8162 is built to survive the hard knocks and harsh weather environments of many type mobile installations. These mobiles meet or exceed the MIL-STD 810 C, D, E, & F environmental standards including the "drip rain" test.*

* MIL-STD compatibility requires the KMC-35 or KMC-36 microphone.

16 CHANNELS

The TK-71 62/8162 has a 16-channel capacity for single or multiple site radio systems.

ENHANCED KENWOOD AUDIO & FRONT MOUNTED SPEAKERS

Equipped with 4W high power front mounted speakers and renowned Kenwood audio technology, the TK-71 62/8162 provides loud clear audio even in noisy environments.

ILLUMINATED LCD DISPLAY

The LCD provides quick recognition of operating status and present settings with numeric characters (0 to 16) and icons. For the night-time viewing, the LCD display and keypads can be illuminated.

LONE WORKER

This ingenious feature provides an extra layer of security and safety for individuals who work remotely as well as for those who work in hazardous areas. As long as the buttons are pressed regularly, the radio operates normally; however, if there is a long lapse (programmable), it will sound an alert. In the absence of further response from the user, the TK-71 62/8162 will place an emergency call to a predetermined person or group of people.

FleetSync® PTT ID

Kenwood's FleetSync® digital signalling system includes PTT ID digital ANI for instant radio call identification and Emergency status for personnel safety.

5-TONE SIGNALLING

In addition to FleetSync® PTT ID, the TK-71 62/8162 includes 5-Tone selective calls in 6-different formats, EIA, EEA, CCIR, ZVEI, ZVEI2 and the Kenwood format.

SCAN

Multi-channel call monitoring can be customized with delete/add scan. Priority Scan automatically checks a primary channel for activity while receiving a call on a non-priority channel. Convenience features such as Priority-channel Stop Tone, Temporary Delete and Revert Channel Display facilitate user-friendly operation and eliminate confusion.

OTHER FEATURES

- QT/DQT, DTMF
- Voting
- Voice Inversion Scrambler
- Programmable Function Keys
- Programmable Channel Spacing
- Embedded Messages
- Ignition Sense Input & Cable Option
- Horn Alert Option
(External relay unit required)
- Microsoft Windows® PC Programming & Tuning
- Encryption & ANI Control Capability
- Operator Selectable Tone



Options

<p>■ KMC-35 Heavy-duty Microphone</p> 	<p>■ KMC-9C Control Station Desktop Microphone</p> 	<p>■ KES-3 External Speaker</p> 	<p>■ KDS-100 Mobile Data Terminal (requires KCT-39 option)</p> 
<p>■ KMC-36 Heavy-duty Keypad Microphone</p> 	<p>■ KCT-18 Ignition Sense Cable (requires KCT-39 option)</p> 	<p>■ KMB-10 Key Lock Adapter</p> 	<p>■ KGP-2A GPS Receiver Modem (requires KCT-39 option)</p> 
<p>■ KMC-30 Microphone</p> 	<p>■ KCT-36 3m Extension Cable (for KCT-39)</p> 	<p>■ KLF-2 Line Noise Filter</p> 	<p>■ KGP-2B GPS Controller Modem (requires KCT-39 option)</p> 
<p>■ KMC-32 Keypad Microphone</p> 	<p>■ KCT-39 Connection Cable (16-pin)</p> 		

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

	TK-7162	TK-8162		TK-7162	TK-8162
GENERAL			RECEIVER		
Frequency Range			Sensitivity (EIA 12dB SINAD)	0.28 µV / 0.28 µV / 0.35 µV	0.28 µV / 0.28 µV / 0.35 µV
E type	136~174 MHz	440~470 MHz	Sensitivity (EN 20dB SINAD)	-3dB µV / -3dB µV / -2dB µV	-3dB µV / -3dB µV / -2dB µV
E3 type	—	400~430 MHz	25kHz/20kHz*/1 2.5kHz		
Number of Channels	Max.16 channels	Max.16 channels	Adjacent Channel Selectivity	70 dB / 70 dB / 60 dB	70 dB / 70 dB / 60 dB
Channel Spacing	25 kHz / 20 kHz / 12.5 kHz	25 kHz / 20 kHz* / 12.5 kHz	25kHz/20kHz*/1 2.5kHz		
Operating Voltage	13.6 V DC±15 %	13.6 V DC±15 %	Intermodulation	65 dB	65 dB
Current Drain			Spurious Response Rejection	70 dB	70 dB
Standby	0.4 A	0.4 A	Audio Output (4 C impedance)	4 W with less than 5 % distortion	4 W with less than 5 % distortion
Receive	1.0 A	1.0 A	TRANSMITTER		
Transmit	8.0 A	8.0 A	RF Output Power	5 – 25 W	5 – 25 W
Operating Temperature Range	-30 °C ~ +60 °C	-30 °C ~ +60 °C	Modulation Limiting	±5.0 kHz at 25 kHz	±5.0 kHz at 25 kHz
Frequency Stability	±2.5 ppm (-30 °C ~ +60 °C)	±2.5 ppm (-30 °C ~ +60 °C)		±4.0 kHz at 20 kHz	±4.0 kHz at 20 kHz*
Antenna Impedance	50 C	50 C		±2.5 kHz at 12.5 kHz	±2.5 kHz at 12.5 kHz
Channel Frequency Spread			Spurious Emission	-36 dBm~1 GHz, -30 dBm>1 GHz	-36 dBm~1 GHz, -30 dBm>1 GHz
E type	38 MHz	30 MHz	FM Noise (EIA)	45 dB / 40 dB	45 dB / 40 dB
E3 type	—	30 MHz	Modulation Distortion	3 % / 5 %	3 % / 5 %
Dimensions (W x H x D), Projections not included	160 mm x 43 mm x 107 mm	160 mm x 43 mm x 107 mm	Microphone Impedance	600 C	600 C
Weight (net)	1.00 kg	1.00 kg	*TK-8162 E3 type:channel spacing 12.5 kHz / 25 kHz		
Applicable Standards	EN 300 086, EN 300 113, EN 300 219, EN 301 489	EN 300 086, EN 300 113, EN 300 219, EN 301 489	Measurements made per EN Standards.		
E-mark (95/54/EC)			Kenwood follows a policy of continuous advancement in development.		
E type	e11 *72/245*95/54*3016*00	e11 *72/245*95/54*3017*00	For this reason specifications may be changed without notice.		
E3 type	—	e11*72/245*95/54*3018*00	FleetSync® is a registered trademark of Kenwood Corporation.		
			Windows is a registered trademark of Microsoft Corporation in the United States and other countries.		
			All other trademarks are property of their respective owners.		

Applicable MIL-STD

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain*	506.1/Procedure II	506.2/Procedure II	506.3/Procedure II	506.4/Procedure III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V

* Required condition for Drip-Rain: KCT cable and/or SP cable are not connected; KMC-35/36 Microphone is connected.

Communication Specialists Ltd.
Unit 20, Murrell Green Business Park,
London Road, Hook,
Hampshire.
United Kingdom.
RG27 9GR

Tel. +44 (0) 1256 766600
Fax. +44 (0) 1256 766500
www.walkie-talkie.co.uk
info@comm-spec.co.uk