



NIGHT VISION DEVICES

- ISO 9001:2000 REGISTERED FIRM
A CCR Registered Company
- *NATO APPROVED NCAGE : KCU48*
COMMUNICATION SPECIALISTS LTD
- **THE WORLDS PREFERRED
COMMUNICATION PARTNER**





Unit 20 Murrell Green Business Park, London Road, Hook, Hampshire RG27 9GR
T: +44 (0) 1256 766600 F: +44 (0) 1256 766500 GSM: +44 (0) 7770808804/+44 (0) 7791730115
E: info@comm-spec.com & malik@comm-spec.com www.comm-spec.com



Registered Office: 4 High Street, Alton, Hampshire GU34 1BU Registered in England No: 04709360

1.	<p><u>GOGGLES- GEN-II + /GEN-III NVG-GEN-III</u></p> 	<ul style="list-style-type: none"> • It has a two-stage infrared-illuminator with an on/off indicator. Possibility of operation with additional lenses as a night binocular. The telescopic design provides inter-eye regulation within a wide distance range. Shock-resistant body comprising of light alloys of aluminium <p>specification.</p> <table> <tr> <td>Lenses, focal length, mm</td> <td>F26</td> </tr> <tr> <td>Angle of vision, degree</td> <td>40</td> </tr> <tr> <td>Focus limit, m</td> <td>0,25 ... ∞</td> </tr> <tr> <td>Diopter range, D</td> <td>± 4</td> </tr> <tr> <td>Type of batteries</td> <td>2 x AA</td> </tr> <tr> <td>Operating time (without IR), hour</td> <td>40</td> </tr> <tr> <td>Dimensions, mm</td> <td>148x117x56</td> </tr> <tr> <td>Weight, kg</td> <td>0,52</td> </tr> <tr> <td>Image intensifier tube, generation</td> <td>2+</td> </tr> </table>	Lenses, focal length, mm	F26	Angle of vision, degree	40	Focus limit, m	0,25 ... ∞	Diopter range, D	± 4	Type of batteries	2 x AA	Operating time (without IR), hour	40	Dimensions, mm	148x117x56	Weight, kg	0,52	Image intensifier tube, generation	2+
Lenses, focal length, mm	F26																			
Angle of vision, degree	40																			
Focus limit, m	0,25 ... ∞																			
Diopter range, D	± 4																			
Type of batteries	2 x AA																			
Operating time (without IR), hour	40																			
Dimensions, mm	148x117x56																			
Weight, kg	0,52																			
Image intensifier tube, generation	2+																			
2.	<p><u>GOGGLES- GII-II+/GEN-III NVG-GIII</u></p> 	<table> <tr> <td>Lenses, focal length, mm</td> <td>F26</td> </tr> <tr> <td>Angle of vision, degree</td> <td>40</td> </tr> <tr> <td>Focus limit, m</td> <td>0,25 ... ∞</td> </tr> <tr> <td>Diopter range, D</td> <td>± 4</td> </tr> <tr> <td>Type of batteries</td> <td>CR123A Lithium</td> </tr> <tr> <td>Operating time (without IR), hour</td> <td>30</td> </tr> <tr> <td>Dimensions, mm</td> <td>117x112x58</td> </tr> <tr> <td>Weight, kg</td> <td>0,65</td> </tr> <tr> <td>Image intensifier tube, generation</td> <td>2+</td> </tr> </table>	Lenses, focal length, mm	F26	Angle of vision, degree	40	Focus limit, m	0,25 ... ∞	Diopter range, D	± 4	Type of batteries	CR123A Lithium	Operating time (without IR), hour	30	Dimensions, mm	117x112x58	Weight, kg	0,65	Image intensifier tube, generation	2+
Lenses, focal length, mm	F26																			
Angle of vision, degree	40																			
Focus limit, m	0,25 ... ∞																			
Diopter range, D	± 4																			
Type of batteries	CR123A Lithium																			
Operating time (without IR), hour	30																			
Dimensions, mm	117x112x58																			
Weight, kg	0,65																			
Image intensifier tube, generation	2+																			





<p>3.</p>	<p><u>BINOCULARS– GEN-II+/GENIII , NVB-GEN-III</u></p> 	<ul style="list-style-type: none"> • Better comfort for using at night and during a day, wide-aperture optics, shock-resistant body comprising of light alloys of aluminium, built-in illuminator, interpupillary adjustment has wide range. <p><u>Specification</u></p> <table border="1"> <thead> <tr> <th>Model</th> <th>"Night"</th> <th>"Day"</th> </tr> </thead> <tbody> <tr> <td>Lenses, focal length, mm</td> <td>F100</td> <td>F100</td> </tr> <tr> <td>Magnification, X</td> <td>5</td> <td>5</td> </tr> <tr> <td>Angle of vision, degree</td> <td>9</td> <td>9</td> </tr> <tr> <td>Interpupillary Distance, mm</td> <td>59...70</td> <td>59...70</td> </tr> <tr> <td>Diopter range, dptr.</td> <td>± 4</td> <td>± 4</td> </tr> <tr> <td>Type of batteries</td> <td>CR123A-Lithium</td> <td>-</td> </tr> <tr> <td>Operating time (without IR), hour</td> <td>36</td> <td>∞</td> </tr> <tr> <td>Dimensions, mm</td> <td>265x135x64</td> <td>265x135x64</td> </tr> <tr> <td>Weight, kg</td> <td>1,3</td> <td>1,3</td> </tr> <tr> <td>Image intensifier tube, generation</td> <td>2+</td> <td>2+</td> </tr> </tbody> </table>	Model	"Night"	"Day"	Lenses, focal length, mm	F100	F100	Magnification, X	5	5	Angle of vision, degree	9	9	Interpupillary Distance, mm	59...70	59...70	Diopter range, dptr.	± 4	± 4	Type of batteries	CR123A-Lithium	-	Operating time (without IR), hour	36	∞	Dimensions, mm	265x135x64	265x135x64	Weight, kg	1,3	1,3	Image intensifier tube, generation	2+	2+																											
Model	"Night"	"Day"																																																												
Lenses, focal length, mm	F100	F100																																																												
Magnification, X	5	5																																																												
Angle of vision, degree	9	9																																																												
Interpupillary Distance, mm	59...70	59...70																																																												
Diopter range, dptr.	± 4	± 4																																																												
Type of batteries	CR123A-Lithium	-																																																												
Operating time (without IR), hour	36	∞																																																												
Dimensions, mm	265x135x64	265x135x64																																																												
Weight, kg	1,3	1,3																																																												
Image intensifier tube, generation	2+	2+																																																												
<p>4.</p>	<p><u>BINOCULARS– GEN-II+/GEN-III , NVB-GEN-III</u></p> 	<table border="1"> <thead> <tr> <th></th> <th>F80</th> <th>F64</th> <th>F50</th> <th>F35</th> </tr> </thead> <tbody> <tr> <td>Lenses, focal length, mm</td> <td>F80</td> <td>F64</td> <td>F50</td> <td>F35</td> </tr> <tr> <td>Magnification, X</td> <td>3,2</td> <td>2,5</td> <td>2</td> <td>1,5</td> </tr> <tr> <td>Angle of vision, degree</td> <td>13</td> <td>16</td> <td>20</td> <td>30</td> </tr> <tr> <td>Focus limit, m</td> <td>5 ... ∞</td> <td>5 ... ∞</td> <td>5 ... ∞</td> <td>5 ... ∞</td> </tr> <tr> <td>Diopter range, dptr.</td> <td>± 4</td> <td>± 4</td> <td>± 4</td> <td>± 4</td> </tr> <tr> <td>Type of batteries</td> <td>CR123A-Lithium</td> <td>CR123A-Lithium</td> <td></td> <td>CR123A-</td> </tr> <tr> <td>Lithium, CR-123A-Lithium</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Operating time (without IR), hour</td> <td></td> <td>30</td> <td>30</td> <td>30</td> </tr> <tr> <td>Dimensions, mm</td> <td>185x124x64</td> <td>172x116x64</td> <td>153x111x58</td> <td>43x111x58</td> </tr> <tr> <td>Weight, kg</td> <td>1,0</td> <td>1,02</td> <td>0,80</td> <td>0,75</td> </tr> <tr> <td>Image intensifier tube, generation</td> <td>2+</td> <td>2+</td> <td>2+</td> <td>2+</td> </tr> </tbody> </table>		F80	F64	F50	F35	Lenses, focal length, mm	F80	F64	F50	F35	Magnification, X	3,2	2,5	2	1,5	Angle of vision, degree	13	16	20	30	Focus limit, m	5 ... ∞	5 ... ∞	5 ... ∞	5 ... ∞	Diopter range, dptr.	± 4	± 4	± 4	± 4	Type of batteries	CR123A-Lithium	CR123A-Lithium		CR123A-	Lithium, CR-123A-Lithium					Operating time (without IR), hour		30	30	30	Dimensions, mm	185x124x64	172x116x64	153x111x58	43x111x58	Weight, kg	1,0	1,02	0,80	0,75	Image intensifier tube, generation	2+	2+	2+	2+
	F80	F64	F50	F35																																																										
Lenses, focal length, mm	F80	F64	F50	F35																																																										
Magnification, X	3,2	2,5	2	1,5																																																										
Angle of vision, degree	13	16	20	30																																																										
Focus limit, m	5 ... ∞	5 ... ∞	5 ... ∞	5 ... ∞																																																										
Diopter range, dptr.	± 4	± 4	± 4	± 4																																																										
Type of batteries	CR123A-Lithium	CR123A-Lithium		CR123A-																																																										
Lithium, CR-123A-Lithium																																																														
Operating time (without IR), hour		30	30	30																																																										
Dimensions, mm	185x124x64	172x116x64	153x111x58	43x111x58																																																										
Weight, kg	1,0	1,02	0,80	0,75																																																										
Image intensifier tube, generation	2+	2+	2+	2+																																																										



4.	<p><u>MONOCULARS- GEN-II+/GEN-III, NVM-GEN-III</u></p> 	<p>Compactness. There are several replaceable lenses to obtain various optical magnifications. Built-in IR-illuminator. Can be fitted to a head-mask and used as night vision goggles, giving 'hands-free' operation. Shock-resistant body comprising of light alloys of aluminium. An on/off indicator and an on/off indicator for the infrared-illuminator in the ocular</p> <table border="1"> <tr> <td>Lenses, focal length, mm</td> <td>F27</td> <td>F50</td> <td>F80</td> <td>F100</td> <td>F120</td> </tr> <tr> <td>Magnification, X</td> <td>1</td> <td>2</td> <td>3,2</td> <td>4</td> <td>5</td> </tr> <tr> <td>Angle of vision, degree</td> <td>40</td> <td>20</td> <td>13</td> <td>11</td> <td>9</td> </tr> <tr> <td>Focus limit, m</td> <td>0,25 ... ∞</td> <td>5 ... ∞</td> <td>5 ... ∞</td> <td>5 ... ∞</td> <td>5 ... ∞</td> </tr> <tr> <td>Diopter range, dptr.</td> <td>± 4</td> <td>± 4</td> <td>± 4</td> <td>± 4</td> <td>± 4</td> </tr> <tr> <td>Type of batteries</td> <td>CR123A-</td> <td>CR123A-</td> <td>CR123A-</td> <td>CR123A</td> <td>CR123A</td> </tr> <tr> <td></td> <td>Lithium</td> <td>Lithium</td> <td>Lithium</td> <td>Lithium</td> <td>Lithium</td> </tr> <tr> <td>Operating time (without IR), hour</td> <td>36</td> <td>36</td> <td>36</td> <td>36</td> <td>36</td> </tr> <tr> <td>Dimensions, mm</td> <td colspan="5">133x48x69, 162x48x69, 192x58x74, 239x63x77, 264x63x77</td> </tr> <tr> <td>Weight, kg</td> <td>0,39</td> <td>0,48</td> <td>0,57</td> <td>0,68</td> <td>0,7</td> </tr> <tr> <td>Image intensifier tube,</td> <td>2+</td> <td>2+</td> <td>2+</td> <td>2+</td> <td>2+</td> </tr> </table>	Lenses, focal length, mm	F27	F50	F80	F100	F120	Magnification, X	1	2	3,2	4	5	Angle of vision, degree	40	20	13	11	9	Focus limit, m	0,25 ... ∞	5 ... ∞	5 ... ∞	5 ... ∞	5 ... ∞	Diopter range, dptr.	± 4	± 4	± 4	± 4	± 4	Type of batteries	CR123A-	CR123A-	CR123A-	CR123A	CR123A		Lithium	Lithium	Lithium	Lithium	Lithium	Operating time (without IR), hour	36	36	36	36	36	Dimensions, mm	133x48x69, 162x48x69, 192x58x74, 239x63x77, 264x63x77					Weight, kg	0,39	0,48	0,57	0,68	0,7	Image intensifier tube,	2+	2+	2+	2+	2+
Lenses, focal length, mm	F27	F50	F80	F100	F120																																																															
Magnification, X	1	2	3,2	4	5																																																															
Angle of vision, degree	40	20	13	11	9																																																															
Focus limit, m	0,25 ... ∞	5 ... ∞	5 ... ∞	5 ... ∞	5 ... ∞																																																															
Diopter range, dptr.	± 4	± 4	± 4	± 4	± 4																																																															
Type of batteries	CR123A-	CR123A-	CR123A-	CR123A	CR123A																																																															
	Lithium	Lithium	Lithium	Lithium	Lithium																																																															
Operating time (without IR), hour	36	36	36	36	36																																																															
Dimensions, mm	133x48x69, 162x48x69, 192x58x74, 239x63x77, 264x63x77																																																																			
Weight, kg	0,39	0,48	0,57	0,68	0,7																																																															
Image intensifier tube,	2+	2+	2+	2+	2+																																																															
5.	<p><u>MONOCULARS- GEN-II +/GEN-III, NVM-GEN-III</u></p> 	<p>• Compactness. There are several replaceable lenses to obtain various optical magnifications. Built-in IR-illuminator. Can be fitted to a head-mask and used as night vision goggles, giving 'hands-free' operation. Shock-resistant body comprising of light alloys of aluminium. An on/off indicator and an on/off indicator for the infrared-illuminator in the ocular.</p> <table border="1"> <tr> <td>Lenses, focal length, mm</td> <td>F27</td> <td>F80</td> </tr> <tr> <td>Magnification, X</td> <td>1</td> <td>3,2</td> </tr> <tr> <td>Angle of vision, degree</td> <td>40</td> <td>13</td> </tr> <tr> <td>Focus limit, m</td> <td>0,25 ... ∞</td> <td>5 ... ∞</td> </tr> <tr> <td>Diopter range, dptr.</td> <td>± 4</td> <td>± 4</td> </tr> <tr> <td>Type of batteries</td> <td>CR123A- LITHIUM</td> <td>CR123A- LITHIUM</td> </tr> <tr> <td>Operating time (without IR), hour</td> <td>36</td> <td>36</td> </tr> <tr> <td>Dimensions, mm</td> <td>133x47x67</td> <td>192x58x73</td> </tr> <tr> <td>Weight, kg</td> <td>0,38</td> <td>0,55</td> </tr> <tr> <td>Image intensifier tube, generation</td> <td>2+</td> <td>2+</td> </tr> </table>	Lenses, focal length, mm	F27	F80	Magnification, X	1	3,2	Angle of vision, degree	40	13	Focus limit, m	0,25 ... ∞	5 ... ∞	Diopter range, dptr.	± 4	± 4	Type of batteries	CR123A- LITHIUM	CR123A- LITHIUM	Operating time (without IR), hour	36	36	Dimensions, mm	133x47x67	192x58x73	Weight, kg	0,38	0,55	Image intensifier tube, generation	2+	2+																																				
Lenses, focal length, mm	F27	F80																																																																		
Magnification, X	1	3,2																																																																		
Angle of vision, degree	40	13																																																																		
Focus limit, m	0,25 ... ∞	5 ... ∞																																																																		
Diopter range, dptr.	± 4	± 4																																																																		
Type of batteries	CR123A- LITHIUM	CR123A- LITHIUM																																																																		
Operating time (without IR), hour	36	36																																																																		
Dimensions, mm	133x47x67	192x58x73																																																																		
Weight, kg	0,38	0,55																																																																		
Image intensifier tube, generation	2+	2+																																																																		



6.	<p>ACCESSORIES</p> 	<p>Replaceable lenses enable to change magnification of the devices and range of vision and transform goggles into binocular and vice versa.</p>
7.	<p>HEAD-MASK</p> 	<p>The leader of consumer demand in the market of night vision accessories. Light-weight, convenient, universal head-mask of an original design allows to fasten goggles and monocular on a head to adjust position of devices concerning eyes and provides their fast taking off with fixing in vertical position.</p>





**UNIT 20, MURRELL GREEN BUSINESS PARK
LONDON ROAD,
HOOK, HANTS
RG27 9GR**

**TEL: + 44 (0)1256 766600
FAX: + 44 (0)1256 766500
GSM: + 44 (0)7791730115
+ 44 (0)7770808804**

**E-mail : malik@comm-spec.com
WEBSITE : WWW.COMM-SPEC.COM**



Unit 20 Murrell Green Business Park, London Road, Hook, Hampshire RG27 9GR
T: +44 (0) 1256 766600 F: +44 (0) 1256 766500 GSM: +44 (0) 7770808804/+44 (0) 7791730115
E: info@comm-spec.com & malik@comm-spec.com www.comm-spec.com

Registered Office: 4 High Street, Alton, Hampshire GU34 1BU Registered in England No: 04709360